



To change the current search results from Status (default) Age/Sex or Location to Age/Sex/Location as per the sample above, do the following:

1. Go to Admin/Settings/Advanced Settings/Profile Member Brief Info (Third last field on page)
2. Select Age + Sex
3. Save
4. Go to /inc/classes/BxDolMemberinfo.php
5. Provided you haven't made any prior alterations to the file, go to Line **87** or search for case 'sys_age_sex':
6. Replace this section:

```
87 case 'sys_age_sex':
88     $s = ('0000-00-00' == $aData['DateOfBirth'] ? '' : _t('_y/o', age($aData[
      'DateOfBirth']))) . (empty($aData['Sex']) ? '' : ' ' . _t('_' . $aData['Sex']));
89     if ($aData['Couple'] > 0) {
90         $aData2 = getProfileInfo($aData['Couple']);
91         $s .= '<br />' . ('0000-00-00' == $aData2['DateOfBirth'] ? '' : _t('_y/o',
      age($aData2['DateOfBirth']))) . (empty($aData2['Sex']) ? '' : ' ' . _t('_' .
      $aData2['Sex']));
92     }
93     return $s;
```

7. With this

The actual code is attached as a text document. Just do a copy and paste.

```
87 case 'sys_age_sex':
88     $s = ('0000-00-00' == $aData['DateOfBirth'] ? '' : _t('_y/o', age($aData[
      'DateOfBirth']))) . (empty($aData['Sex']) ? '' : ' ' . _t('_' . $aData['Sex']) .
      '<br>' .
89
90     (empty($aData['City']) ? '' : htmlspecialchars_adv($aData['City']) . ', ' . _t(
      $GLOBALS['aPreValues']['Country'][$aData['Country']]['LKey']));
91
92     if ($aData['Couple'] > 0) {
93         $aData2 = getProfileInfo($aData['Couple']);
94         $s .= '<br />' . ('0000-00-00' == $aData2['DateOfBirth'] ? '' : _t('_y/o',
      age($aData2['DateOfBirth']))) . (empty($aData2['Sex']) ? '' : ' ' . _t('_' .
      $aData2['Sex']) .
95
96     (empty($aData['City']) ? '' : htmlspecialchars_adv($aData['City']) . ', ' . _t(
      $GLOBALS['aPreValues']['Country'][$aData['Country']]['LKey']));
97     }
98     return $s;
```

8. To change the Age from xx y/o, Man to Male and Woman to female, you need to change the language keys at Admin/Settings//Languages Settings:
9. y/o is a Language Key. Search for _y/o and change the string to {0} / (Do not change the keyname _y/o)
10. Man is a Language Key. Search for _male and change the string from Man to Male (Do not change the key _male)
11. Woman is a Language Key. Search for _Female and change it from Woman to Female (Do not change the key _Female)
12. Save
13. Clear the Cache and run.
14. Always use a test site and don't make any other changes.